

TECHNICAL DATA

PART NUMBER: SCP-5282-36, REV A

**High Pulse Power Mil-STD-1275 & ISO-16750-2 SuperClamp
(Below 40V at 110A)**

Key Features:

- Clamping below 40V DC for 100V, and 250V pulses
- High Pulse Power Capability
- Unidirectional
- Designed for safe paralleling
- Precision Clamping



Applications:

- +28V DC systems
- Enables compliance with MIL-STD-1275, ISO-16750-2 requirements for Injected Surges and Spikes

Protection Level:

- MIL-STD-1275 Compliant for surges - 100V Surge withstanding for 100 msec with 0.5-ohm source impedance, clamping below 40V.
- ISO-16750-2 Load Dump Compliant; 202V with source impedance above 2 ohms, or 151V source impedance above 1 ohm, Surge withstanding for 350 msec.
- Two or more devices may be connected in parallel for clamping currents above 100A.
- Designed to meet SAE J1113-11 under following conditions:
 - ✓ 174V, 2-ohm up to 150msec
 - ✓ 174V, 5-ohm up to 350msec
- 100% tested for 10-msec single pulse from 1A up to 110A followed by 50 msec, 5 pulses, at 1 sec intervals at 100A

Part Ordering Information:

- SCP-5282-36

SENSITRON

SEMICONDUCTOR

SCP-5282-36

TECHNICAL DATA
PART NUMBER: SCP-5282-36, REV A

TECHNICAL DATA (All parameters are at Tc = 25°C unless otherwise specified)

Rating	Condition	Symbol	Min	Typ	Max	Units
Peak Pulse Power Dissipation	1ms	P _{pk}	-		10	KW
Steady State Power Dissipation	-	P	-		150	Watts
Reverse Stand-Off Voltage	-	V _{WM}	-	28	34	Volts
Reverse Leakage. from + to -	@ 28V	I _D	4.0	5.2	10 ⁽¹⁾	mA
Reverse Leakage. from + to -	@ 34V	I _D	5.0	7.0	12 ⁽¹⁾	mA
Reverse Leakage. from + to -	@ 36V	I _D	6	12	20	mA
Reverse Clamping Voltage, from + to -	@ 1A	V _{clamp}	36.45	36.61	36.85	Volts
	@ 10A		36.60	36.80	37.00	
	@ 50A		37.32	37.62	37.92	
	@ 100A		38.35	38.65	39.00	
	@ 110A		38.45	38.85	39.35	
Peak Pulse Current Tc up to 50 °C (single 100-msec square pulse)	-	I _{PP}			100 ⁽²⁾⁽³⁾	Amps
Typical V _{clamp} vs. Current (pulse width limited by conditions above)	@ 0 to 120A		36.59 + 0.02056 * I _{clamp} ⁽²⁾			V
Forward Clamping Voltage, from - to +	@ 10A	V _c	1	1.7	2.8	V
Operating & Storage Temp.	-	T _{op} & T _{stg}	-55		+ 150	°C

Notes:

- (1) This is the maximum leakage at T_A of 85C ambient.
- (2) Device should be mounted to a heat sink if pulses are repeated.
- (3) For Tc above 50 C, derate linearly up 150C as shown in Fig. 1.

TECHNICAL DATA
PART NUMBER: SCP-5282-36, REV A




Fig. 1 - Power Derating Curve




Fig. 2 Unidirectional Clamp Part number SCP-5282-36.


SENSITRON

SEMICONDUCTOR

SCP-5282-36

TECHNICAL DATA
PART NUMBER: SCP-5282-36, REV A

MECHANICAL OUTLINE



TOLERANCE
.XX = ±.020
.XXX = ±.010

DISCLAIMER:

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the Sensitron Semiconductor sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall Sensitron Semiconductor be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). Sensitron Semiconductor assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall Sensitron Semiconductor be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or Sensitron Semiconductor.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of Sensitron Semiconductor.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.